

Specifications

Current Rating:7A AC, DC

Voltage Rating: 250V AC Maximum

Operating Temp: -25°C ~ +85°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Material: Nylon 66, UL94V-0

Part No.	Color
CV-H3961-XX	White
CV-H3961-XXR	Red
CV-H3961-XXY	Yellow
CV-H3961-XXBL	Blue
CV-H3961-XXB	Black



Poles	Dimension mm (in.)	
	A	B
02	3.96 (0.156)	8.04 (0.317)
03	7.92 (0.312)	12.10 (0.476)
04	11.88 (0.468)	15.96 (0.628)
05	15.84 (0.624)	20.00 (0.787)
06	19.80 (0.780)	23.90 (0.941)
07	23.76 (0.935)	27.90 (1.098)
08	27.72 (1.074)	31.86 (1.254)
09	31.68 (1.247)	35.88 (1.413)
10	35.64 (1.403)	39.84 (1.569)
11	39.60 (1.559)	43.74 (1.722)
12	43.56 (1.715)	47.74 (1.880)
13	47.52 (1.871)	51.70 (2.035)
14	51.48 (2.027)	55.66 (2.191)
15	55.44 (2.182)	59.62 (2.347)

※備註：15Pin為特殊Pin數，下單時須有M.O.Q

